



NANOPAK FEATURES

GENERAL

- VITA-74 Derivative
- All I/O through front panel connector

CPU AND MEMORY

- Intel Atom N455 @ 1.66 GHz
- 512 KB DDR2 SDRAM @ 667 MHz
- Dimensions 89 mm (W) X 21 mm (H) X 90 mm (D)
- Weight .2 kg (typical system)
- Linux® and Microsoft Windows®

ENVIRONMENTAL

- Conduction Cooled
- Operating Temperature -40° C to + 85° C

MILITARY SPECIFICATION

- MIL-STD-810G, MIL-STD-461F

NanoPAK

Small Form Factor Computer

The small, light footprint and powerful performance of the NanoPAK small form factor computer make it an ideal solution for rugged commercial and military field applications. This compact, mobile standalone rugged computer is designed to survive in demanding environments. The NanoPAK supports a myriad of field applications that include real time control, data recorders, small storage and communications systems, and mobile robotics.

The first NanoPAK system integrates the Intel Atom processor and FLASH storage in a small, light footprint that optimizes size, weight, power, and cooling. Leveraging thermal and kinetic management design expertise, the NanoPAK boasts a hardened-aluminum conduction-cooled chassis, designed to withstand extreme environmental conditions. The rugged NanoPAK is ideal for a wide range of mission-critical applications, while its performance and cost-competitive price make it an attractive choice for commercial and industrial use.

TECHNICAL SPECIFICATIONS

PARAMETER	DESCRIPTION
CPU	Intel Atom N455 @1.66 GHz
CPU Cores	1
CPU Threads	2
Chipset	Intel IC8HM
SDRAM	512 MB DDR2 @ 667 MHz
FLASH	1 or 2 GB (option)
SATA	1x SATA II
VGA	1x, 1400 x 1050 @ 60 Hz
RS-232	1x TXD/RXD
GigE	1x
USB 2.0	2x
I2C	1x
Audio In	1x
Audio Out	1x
GPIO	2x External I/O
Dimensions	89 mm (W) X 21 mm (H) X 90 mm (D)
Weight	2 Kg (typical system)
Power	18 to 36 VDC @ 7 W (Typical)
Military Specification	MIL-STD-810G, MIL-STD-461F

THEMIS NANO SMALL FORM FACTOR SOLUTIONS

NanoPAK systems are complete, stand alone computer systems designed for various rugged environments including unmanned vehicles, ground vehicles, man-wearable, shipboard and other environments, where space, weight, power and cost are critical. All standard PC interfaces are available, plus others such as MIL-STD-1553, CAN Bus, Discretes, and others. For more information, please contact Themis. Drivers and Board Support Packages are available for Linux® and Windows®. Please contact Themis for information on using other Real Time Operating Systems such as VxWorks®, Integrity® and LynxOS®.

THEMIS VALUE

Themis provides systems manufacturers and end-users with the most modern, best of breed computing resources available. Package and performance scale from small form factor embedded servers to bladed servers. We listen, understand, and work closely with customers to optimize computing solutions that are easy to integrate, inexpensive to own and operate, and that achieve the right balance between standard commercial technology, environmental resiliency, and optimized space, weight, and performance.



Corporate Headquarters
47200 Bayside Parkway
Fremont, CA 94538
Tel: 510-252-0870
Fax: 510-490-5529
www.themis.com

European Sales Office
5 rue Irène Joliot-Curie
38320 Eybens, France
Tel: +33.476.14.77.86
Fax: +33.476.14.77.89

For More Information
Please visit www.themis.com
or contact Themis sales at:
USA +1 (510) 252-0870
Europe +33 (0) 476.14.77.86

©2011 Themis Computer. All rights reserved. Themis Computer, Themis, the Themis logo, NanoATR are trademarks or registered trademarks of Themis Computer. All other trademarks are the property of their respective owners. Themis reserves the right to change the specifications in this document without notice. All rights reserved.
To ensure you have the latest version of the document, please go to www.themis.com.