



Product Information

SN3-GONG

CompactPCI® Serial • Dual-Port 10GBASE-T Ethernet NIC

Document No. 7634 • 19 January 2015



General

The SN3-GONG is a peripheral slot card for CompactPCI® Serial systems. The board is equipped with an Intel® X540 10GBASE-T Ethernet controller, and two RJ45 front panel jacks for attachment of Cat 6 or Cat 6A cables up to 100m length. The ability to auto-negotiate between 100Mbps, 1Gbps, and 10Gbps speeds provides the backwards compatibility for a smooth transition and easy migration to 10GbE.

The X540 is based on PCI Express® 2.1 (up to 5GT/s) and supports x1, x2, x4 and x8 link widths. For optimum performance, the SN3-GONG should be installed in a CompactPCI® Serial fat pipe slot.

The SN3-GONG is well suited for high performance industrial networking applications. Drivers are available for all major operation systems.



Feature Summary


- ▶ PICMG® CompactPCI® Serial (CPCI-S.0) peripheral slot card
- ▶ Single Size Eurocard 3U 4HP 100x160mm²
- ▶ cPCI-S backplane connectors P1 & P2
- ▶ Suitable for PCIe x 1 to PCIe x 8 standard peripheral slots, and fat pipe peripheral slots

- ▶ Gigabit Ethernet controller Intel® X540
- ▶ Link modes 10GBASE-T, 1000BASE-T, and 100BASE-T (IEEE 802.3an, 802.3, 802.3u, and 802.3ab)
- ▶ IEEE 802.3an auto-negotiation for automatic link configuration (speed, duplex, flow control)
- ▶ Automatic cross-over detection function (MDI/MDI-X)
- ▶ Automatic cable diagnostics
- ▶ IEEE 802.3x and 802.3z compliant flow control support
- ▶ Data Center Bridging (DCB) support 802.1Qaz, 802.1Qbb
- ▶ IEEE 802.1Q (VLAN), IEEE 802.1ad (Double VLAN)
- ▶ Hardware-based time stamping (IEEE 1588) and support for 802.1AS - Precise Timing Protocol
- ▶ 15.5KB Jumbo Frame support
- ▶ Rich feature set security functions and I/O virtualization
- ▶ Comprehensive offload and performance features e.g. iSCSI, FCoE
- ▶ Driver support for all major operating systems
- ▶ Two front panel connectors RJ45 with integrated magnetics and echo circuit for noise and EMI cancelling

- ▶ Long term availability
- ▶ Rugged solution (coating, sealing, underfilling available on request)
- ▶ RoHS compliant 2002/95/EC
- ▶ Commercial operating temperature range 0°C to +70°C
- ▶ Industrial operating temperature range -40°C to +85°C on request
- ▶ Storage temperature -40°C to +85°C, max. gradient 5°C/min
- ▶ Humidity 5% ... 95% RH non condensing
- ▶ Altitude -300m ... +3000m
- ▶ Shock 15g 0.33ms, 6g 6ms
- ▶ Vibration 1g 5-2000Hz
- ▶ MTBF tbd
- ▶ EC Regulations EN55022, EN55024, EN60950-1 (UL60950-1/IEC60950-1)


items are subject to changes

Block Diagram




© EKF
ekf.com

Component Assembly



Front Panel



© EKF • draft - do not scale • ekf.com

SN3-GONG
2-Port NIC
10GBASE-T

RJ45 Connectors

10 Gigabit Ethernet			
270.11.08.01 Single RJ45 Jack (2 pos)			
<p>10GBASE-T RJ45</p> <p>1</p> <p>Part #270.11.08.01 draft - do not scale • © EKF • www.ekf.com</p> <p>Upper LEDs: yellow=10Gbit/s green=1Gbit/s</p> <p>Lower LED: on=link established blinking=activity (data)</p>	Ports 1-2	1	MDX0+
		2	MDX0-
		3	MDX1+
		4	MDX2+
		5	MDX2-
		6	MDX1-
		7	MDX3+
		8	MDX3-

P1 CompactPCI® Serial Backplane Connector

P1 CompactPCI® Serial Peripheral Slot Backplane Connector												
EKF Part #250.3.1206.20.02 • 72 pos. 12x6, 14mm Width												
P1	A	B	C	D	E	F	G	H	I	J	K	L
6	GND	1 PE TX02+	1 PE TX02-	GND	1 PE RX02+	1 PE RX02-	GND	1 PE TX03+	1 PE TX03-	GND	1 PE RX03+	1 PE RX03-
5	1 PE TX00+	1 PE TX00-	GND	1 PE RX00+	1 PE RX00-	GND	1 PE TX01+	1 PE TX01-	GND	1 PE RX01+	1 PE RX01-	GND
4	GND	<i>1_</i> <i>USB2+</i>	<i>1_</i> <i>USB2-</i>	GND	PE_CLK IN+	PE_CLK IN-	GND	<i>1</i> SATA TX+	<i>1</i> SATA TX-	GND	<i>1</i> SATA RX+	<i>1</i> SATA RX-
3	<i>1</i> USB3 TX+	<i>1</i> USB3 TX-	GA0	<i>1</i> USB3 RX+	<i>1</i> USB3 RX-	GA1	SATA SDI	SATA SDO	GA2	SATA SCL	SATA SL	GA3
2	GND	I2C SCL	I2C SDA	GND	<i>RSV</i>	<i>RSV</i>	GND	RST#	WAKE#	GND	PE_ EN#	SYS EN#
1	+12V	<i>STBY</i>	GND	+12V	+12V	GND	+12V	+12V	GND	+12V	+12V	GND

pin positions printed italic/gray: not connected

For signal descriptions please refer to PICMG CPCI-S.0 R1.0 CompactPCI® Serial Specification

P2 CompactPCI® Serial Backplane Connector

P2 CompactPCI® Serial Fat Pipe Peripheral Slot Backplane Connector												
EKF Part #250.3.1208.20.00 • 96 pos. 12x8, 16mm Width												
P2	A	B	C	D	E	F	G	H	I	J	K	L
8	GND	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>
7	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>	GND
6	GND	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>
5	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>	GND
4	GND	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>
3	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>	GND	<i>IO</i>	<i>IO</i>	GND
2	GND	1 PE TX06+	1 PE TX06-	GND	1 PE RX06+	1 PE RX06-	GND	1 PE TX07+	1 PE TX07-	GND	1 PE RX07+	1 PE RX07-
1	1 PE TX04+	1 PE TX04-	GND	1 PE RX04+	1 PE RX04-	GND	1 PE TX05+	1 PE TX05-	GND	1 PE RX05+	1 PE RX05-	GND

pin positions printed italic/white: not connected

For signal descriptions please refer to PICMG CPCI-S.0 R1.0 CompactPCI® Serial Specification

SN3-GONG Links

SN3-GONG Home	www.ekf.com/s/sn1/sn1.html
Intel® I210/I211 Driver Download	www.ekf.com/s/sn1/sn1.html
CompactPCI® Serial Ethernet Switches	www.ekf.com/s/serial.html#SL
CompactPCI® Serial Ethernet Controllers	www.ekf.com/s/serial.html#SN
CompactPCI® Serial Overview	www.ekf.com/s/serial_concise.pdf
CompactPCI® Serial - All You Need to Know	www.ekf.com/s/smart_solution.pdf

Ordering Information

For popular SN3-GONG SKUs please refer to
www.ekf.com/liste/liste_21.html#SN1





Industrial Computers Made in Germany
boards. systems. solutions.

EKF Elektronik GmbH
Philipp-Reis-Str. 4 (Haus 1)
Lilienthalstr. 2 (Haus 2)
59065 HAMM
Germany



Phone +49 (0)2381/6890-0
Fax +49 (0)2381/6890-90
Internet www.ekf.com
E-Mail sales@ekf.com