



DST CONTROL

FIREFLY

HAND CONTROL UNIT



Live video view

Complete gimbal control

Sunlight readable

User friendly



FIREFLY

HAND CONTROL UNIT

Features

- Ergonomic
- Sunlight readable display
- Mechanical buttons
- Force joysticks
- Rotary encoders
- Context dependent controls
- Optional battery package
- Optional wireless interface
- Optional video recording



Technical Specifications	
Overview	
Screen Resolution	800 x 480 widescreen
Screen Brightness	500 nits
Power Requirements	18 to 36 VDC
Power Consumption	15 Watt
Battery Type	Li-Ion (optional)
Operational Temperature	-40 °C - 50 °C
Storage Temperature	-40 °C - 70 °C
Weight	1-3 kg, depending on configuration
Connections	Up to 3 different connection types Wifi (optional)
Recorder	Flash disc recorder, optional - SD (PAL/NTSC) - HD
Dimensions	
Width	265 mm
Height	165 mm
Depth	35 mm

The purpose-built FIREFLY Hand Control Unit (HCU) delivers superior control abilities for the DST series of gimbal products.

The FIREFLY Hand Control Unit features a sunlight readable display. The unit is ergonomically designed with anti-slip treated surface and dual axis force joysticks that are ideal to use even under the most demanding conditions, such as inside a helicopter cockpit.

The FIREFLY Hand Control Unit can be combined with an optional HD recorder for video recording. The optional wireless interface pack allows you to stream high-quality video and control signals from a nearby ground station which gives you the freedom to work without cables. The optional dual battery pack gives you the endurance for several hours of continuous use without the need of external power.

