


G227

PCIe Mini Card Carrier for Wireless Functions 3U CompactPCI Serial

- » 2 PCI Express Mini Card slots for LTE, UMTS, GSM, HSPA communication
- » 2 external antennas per module (reverse SMA)
- » 1 PCI Express Mini Card slot for WLAN, GPS, virtual SIM card, audio codec
- » 1 external antenna optional
- » 10 microSIM card slots
- » Software tool for switching SIM cards and remote power up/down of modems
- » -40°C to +85°C screened, conformal coating
- » PICMG CPCI-S.0 CompactPCI Serial peripheral card



The G227 is a rugged single slot CompactPCI Serial carrier board for up to three PCI Express Mini Cards. Two PCI Express Mini Card slots are by default equipped with two RP-SMA antenna connectors / cables each. Other types of antenna connectors are available on request. These slots can be used for UMTS, GSM, HSPA, LTE modems.

Fields of Application

The G227 provides connectivity solutions to cellular networks by adding LTE, UMTS, GSM or other types of wireless modems.


It is intended for use in various train connectivity applications including onboard WLAN, passenger infotainment and fleet management systems. In the train communication system architecture, the G227 is typically located at the front end where it communicates directly with a cellular network. To optimize the connection and network coverage, the G227 features ten microSIM card slots.

Software

MEN provides a user friendly software tool designed for interacting with the G227. The user is able to remotely control which microSIM cards are connected to the modems. Remote power reset is also possible for each modem and the third optional PCI Express Mini Card module.

Suited for harsh and mobile environments

The G227 is designed for -40 to +85°C operating temperature and conformal coated in order to be used also in harsh and mobile environments. The final environmental qualification depends on the respective PCI Express Mini Cards used with the carrier.



Diagram



Card Interfaces

- Two PCI Express Mini Card slots (only full size)
 - USB 3.0 interface
 - For UMTS, GSM, HSPA, LTE functionality
- One PCI Express Mini Card slot (only full size)
 - USB 2.0 interface
 - PCI Express interface
 - For WLAN, GPS, GLONASS, audio, virtual SIM functionality
- 10 microSIM card holders
- Individual reset and power on/off for each PCI Express Mini Card
 - Via software
- Please note that MEN does not offer SIM cards or mobile telephony contracts!

Front Interfaces

- Four Reverse SMA antenna connectors or
- Five Reverse SMA antenna connectors (on request)
- Other types of antenna connectors (on request)
- Four HF cables
- One power LED and one user LED for each PCI Express Mini card

Backplane Standard

- Compliance with CompactPCI Serial PICMG CPCI-S.0 Specification
- Peripheral slot
- Host connection: one PCI Express x1 link

Electrical Specifications

- Supply voltage:
 - +12 V (-5%/+5%)
- Power consumption:
 - Depending on plugged PCI Express Mini card
 - 2.5 W without PCIe Express Mini cards

Mechanical Specifications

- Dimensions:
 - 3U, 4 HP
- Weight: 172 g (without cards)

Environmental Specifications

- Temperature range (operation):
 - -40°C to +85°C (screened, only carrier, depending on configuration)
 - Airflow: min. 1.5 m/s
- Temperature range (storage): -40°C to +85°C
- Humidity (operation): EN 60068-2-30, EN 50155
- Shock: EN 50155
- Vibration: EN 50155
- Conformal coating

MTBF

- MTBF: 1 722 735 h @ 40°C according to IEC/TR 62380 (RDF 2000)

Safety

- Electrical Safety
 - EN 50155
 - EN 50153
- Flammability (PCBs)
 - UL 94 V-0
- Fire Protection
 - EN 45545-2

EMC

- Radiated Emission: EN 50121-3-2
- Immunity: EN 50121-3-2

Software Support

- Windows
- Linux
- For more information on supported operating system versions and drivers see Software.

Germany

MEN Mikro Elektronik GmbH

Neuwieder Straße 3-7
90411 Nuremberg
Phone +49-911-99 33 5-0

sales@men.de
www.men.de

USA

MEN Micro Inc.

860 Penllyn Blue Bell Pike
Blue Bell, PA 19422
Phone 215-542-9575

sales@menmicro.com
www.menmicro.com

France

MEN Mikro Elektronik SAS

18, rue René Cassin
ZA de la Châtelaine
74240 Gaillard
Phone +33-450-955-312

sales@men-france.fr
www.men-france.fr

China

MEN Mikro Elektronik (Shanghai) Co., Ltd.

Room 808-809, Jiaxing Mansion, No. 877 Dongfang Road
200122 Shanghai
Phone +86-21-5058-0961

sales@men-china.cn
www.men-china.cn

Up-to-date information, documentation and ordering information:

www.men.de/products/g227/

The date of issue stated in this data sheet refers to the Technical Data only. Changes in ordering information given herein do not affect the date of issue. All brand or product names are trademarks or registered trademarks of their respective holders.

MEN is not responsible for the results of any actions taken on the basis of information in the publication, nor for any error in or omission from the publication.

MEN expressly disclaims all and any liability and responsibility to any person, whether a reader of the publication or not, in respect of anything, and of the consequences of anything, done or omitted to be done by any such person in reliance, whether wholly or partially, on the whole or any part of the contents of the publication.

The correct function of MEN products in mission-critical and life-critical applications is limited to the environmental specification given for each product in the technical user manual. The correct function of MEN products under extended environmental conditions is limited to the individual requirement specification and subsequent validation documents for each product for the applicable use case and has to be agreed upon in writing by MEN and the customer. Should the customer purchase or use MEN products for any unintended or unauthorized application, the customer shall indemnify and hold MEN and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim or personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that MEN was negligent regarding the design or manufacture of the part.

In no case is MEN liable for the correct function of the technical installation where MEN products are a part of.

© 2017 MEN Holding